


- High satura on characteris c core for large satura on current and low loss.
- Closed magne c circuit design reduces leakage flux.
- High precision DCR.
- Halogen Free & ROHS compliant.
- Opera ng temperature: -40 to +125 °C

- AI Servers, Data Centers, GPU/AI Accelerators.
- Desktop Motherboards, CPU/GPU Power Delivery.
- Mul -phase VRM, High-current DC-DC Converters.
- Networking Equipment, Communica on Infrastructure.



MDVR090610	9.6 max	6.4 max	10.4 max	3.2 typ	3.2 typ	1.50 typ	1.00 typ
MDVR10056	10.2 max	5.0 max	6.0 max	4.0±0.3	1.4±0.5	1.25 typ	1.20 typ
MDVR120612	12.0 max	6.0 max	12.2 max	2.55 typ	2.55 typ	1.63 typ	1.27 typ



MDVR090610	10.1	3.9	5.8	1.0	3.8	3.8
MDVR10056	10.4	4.4	6.9	1.0	4.5	1.9
MDVR120612	12.2	4.39	7.94	0.85	3.05	3.05

MDVR090610-R15L	150	±15%	71	65	0.125	0.45

MDVR10056F-R12K	120	±10%	40	54	0.29	0.70


MDVR120612-R10K	100	±10%	75	130	0.125	0.37

△

:

Marking	Printing (In $_{d}$uctance)

:



:

-
-
-
-
-
-
-