

NRSE Series
SMD Shielded Tiny Power Inductor
Size 6028

CHARACTERISTICS

- Magnetic resin for high temperature stability
- High inductance

APPLICATION

-
-

Dimensions: [mm]

Land Pattern: [mm]

Electrical Properties:

Part No	Inductance @100KHz/0.25V (μ H)	Tolerance	Satura on current (A)	Temperature Rise Current (A)	DCR $\pm$ 30% (m Ω)
NRSE6028-390M	39	$\pm$ 20%	1.25	1.10	225
NRSE6028-470M	47	$\pm$ 20%	1.15	1.05	280
NRSE6028-680M	68	$\pm$ 20%	0.95	0.85	420
NRSE6028-820M	82	$\pm$ 20%	0.80	0.70	550
NRSE6028-101M	100	$\pm$ 20%	0.65	0.60	670
NRSE6028-121M	120	$\pm$ 20%	0.62	0.58	820


Opera ng temperature : -40 $^{\circ}$ C ~ +125 $^{\circ}$ C

Temperature rise current: the actual value of DC current when the temperature rise is Δ T40 $^{\circ}$ C

Satura on Current that will cause ini al inductance to drop approximately 30%

Typical Electrical Characteristics:

Inductance VS. Current Characteristics:



Temperture Rise VS. Current Characteristics:

